

Document made available under the Patent Cooperation Treaty (PCT)

International application number: PCT/US05/006672

International filing date: 02 March 2005 (02.03.2005)

Document type: Certified copy of priority document

Document details: Country/Office: US
Number: 60/550,972
Filing date: 05 March 2004 (05.03.2004)

Date of receipt at the International Bureau: 07 April 2005 (07.04.2005)

Remark: Priority document submitted or transmitted to the International Bureau in compliance with Rule 17.1(a) or (b)



World Intellectual Property Organization (WIPO) - Geneva, Switzerland
Organisation Mondiale de la Propriété Intellectuelle (OMPI) - Genève, Suisse

1301476



THE UNITED STATES OF AMERICA

TO ALL TO WHOM THESE PRESENTS SHALL COME:

UNITED STATES DEPARTMENT OF COMMERCE

United States Patent and Trademark Office

March 31, 2005

THIS IS TO CERTIFY THAT ANNEXED HERETO IS A TRUE COPY FROM THE RECORDS OF THE UNITED STATES PATENT AND TRADEMARK OFFICE OF THOSE PAPERS OF THE BELOW IDENTIFIED PATENT APPLICATION THAT MET THE REQUIREMENTS TO BE GRANTED A FILING DATE.

APPLICATION NUMBER: 60/550,972

FILING DATE: *March 05, 2004*

RELATED PCT APPLICATION NUMBER: PCT/US05/06672



Certified by

Don W. Dudas

Under Secretary of Commerce
for Intellectual Property
and Director of the United States
Patent and Trademark Office

Please type a plus sign inside this box

Approved for use through 10/31/2002. OMB 0651-0030
 U.S. Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

PROVISIONAL APPLICATION FOR PATENT COVER SHEET

This is a request for filing a PROVISIONAL APPLICATION FOR PATENT under 37 CFR 1.53(c).

Express Mail Label No.

EL 908622907 US

Richard Hark

INVENTOR(S)					
Given Name (first and middle (if any))		Family Name or Surname		Residence (City and either State or Foreign Country)	
Theodore D.		Ciolkosz		362 Adams Street, Milton, MA 02186	
<input checked="" type="checkbox"/> Additional inventors are being named on the <input checked="" type="checkbox"/> separately numbered sheets attached hereto					
TITLE OF THE INVENTION (280 characters max)					
A DEVICE HAVING SEAL COATINGS FOR RECEIVING AND DISCHARGING FLUID					
Direct all correspondence to: CORRESPONDENCE ADDRESS					
<input type="checkbox"/> Customer Number		<input type="text"/>		<input type="text"/>	
OR		Customer Number		Customer Number Bar Code	
<input checked="" type="checkbox"/> Firm or Individual Name		Anthony J. Janiuk, Esq.			
Address		Waters Corporation 34 Maple Street - MS: LG			
City		Milford		State	MA
Country		USA		Zip	01757
		Telephone		(508) 482-2714	Fax (508) 482-2320
ENCLOSED APPLICATION PARTS (check all that apply)					
<input checked="" type="checkbox"/>	Specifications, claims, abstract	15	<input type="checkbox"/>	CD(s), Number	<input type="text"/>
<input checked="" type="checkbox"/>	Figures	3	<input checked="" type="checkbox"/>	Other:	Prepaid Return Postcard
<input type="checkbox"/>	Application Data Sheet. See 37 CFR 1.76				
METHOD OF PAYMENT OF FILING FEES FOR THIS PROVISIONAL APPLICATION FOR PATENT					
<input type="checkbox"/> Applicant claims small entity status. See 37 CFR 1.27.					
<input type="checkbox"/> A check or money order is enclosed to cover the filing fees					
<input checked="" type="checkbox"/> The Commissioner is hereby authorized to charge filing fees or credit any overpayment to Deposit Account Number:					
				23-0503	FILING FEE AMOUNT (\$) 160.00
The invention was made by an agency of the United States Government or under a contract with an agency of the United States Government.					
<input checked="" type="checkbox"/> No <input type="checkbox"/> Yes, the name of the U.S. Government agency and the Government contract number are:					

Respectfully submitted,

SIGNATURE

 TYPED OR
 PRINTED NAME

Anthony J. Janiuk, Esq.

TELEPHONE

(508) 482-2714 fax: (508) 482-2320

Date

March 5, 2004

 REGISTRATION NO.
 (if appropriate)

29,809

Docket Number:

04-361

USE ONLY FOR FILING A PROVISIONAL APPLICATION FOR PATENT

PROVISIONAL APPLICATION PATENT COVER SHEET

SECOND PAGE

ADDITIONAL INVENTORS:

Mark Moeller, 12 Nottingham Drive, Kingston, Massachusetts 02364 USA

Daniel J. McCormick, 1 Blue Ridge Road, Westford, Massachusetts 01886 USA

Charles Murphy, 24 Holbrook Lane, Uxbridge, Massachusetts 01569 USA

Joseph A. Luongo, 7 Saddle Way, Walpole, Massachusetts 02081 USA

Russell Keene, 66 Beechwood Avenue, Sudbury, Massachusetts 01776 USA

Theodore Dourdeville, 29 Bell Guzzle Lane, Marion, Massachusetts 02738

David Friswell, 134 South, Upton, Massachusetts 01568 USA

Peter Kirby, 9 Rocky Circle, Derry, New Hampshire 03038 USA

CERTIFICATE OF MAILING BY "EXPRESS MAIL"
(37 CFR § 1.10) No. EL 908622907 US

APPLICANT(S): WATERS INVESTMENTS LIMITED
Theodore D. Ciolkosz, Mark Moeller, Daniel J. McCormick,
Charles Murphy, Joseph A. Luongo, Russell Keene, Theodore
Dourdeville, David Friswell, Peter Kirby

TITLE OF INVENTION:

A DEVICE HAVING SEAL COATINGS FOR RECEIVING AND
DISCHARGING FLUID

FILING DATE: HEREWITH


ASSIGNEE: WATERS INVESTMENTS LIMITED


APPLICATION NUMBER (if known): UNKNOWN

MAIL STOP- PROVISIONAL APPLICATION

Commissioner for Patents
P.O. Box 1450
Alexandria, VA 22313-1450

I hereby certify that the correspondence identified in the transmittal below is being deposited with the United States Postal Service "Express Mail Post Office to Addressee" service under 37 CFR § 1.10 in an envelope addressed to: Mail Stop Provisional Applications, Commissioner for Patents, P.O. Box 1450, Alexandria, VA 22313-1450 on March 5, 2004.





TRANSMITTAL LETTER

Enclosed for filing in the above identified provisional patent application are the following documents:

Provisional patent application transmittal letter (2 pgs.); specifications including claims and abstract (15 pgs), formal drawings (3 pgs) and prepaid return postcard.

March 5, 2004
Reg. No. 29,809


Anthony J. Janiuk

A DEVICE HAVING SEAL COATINGS FOR
RECEIVING AND DISCHARGING FLUID

5 Embodiments of the present invention are directed to devices and method for coupling, or joining components for receiving and discharging fluids. Devices made in accordance with the present invention have special application to fittings, valves and check valves.

10 BACKGROUND OF THE INVENTION

The present invention is directed to devices for receiving and discharging fluids. Devices embodying features of the present invention include, by way of example, without limitation, tees, unions, fittings, valves and check valves. These devices are sometimes placed in line between two or more conduits that are joined in the form of a union, or tee, or valve. The term "union" is used in the sense of joining or bringing together. A "tee" is a form of fitting in which fluid flow is split or combined. The devices are sometimes part of a larger structure in which the device communicates through ports or openings. This application will use the term "fluid path means" to mean all conduits, tubing, pipes, openings or ports which convey or transport fluids.

In this application, the term fitting will be used in the broadest sense to refer to a device that may be placed in a larger structure, for example, a pump assembly, or in line.

25 The term "valve" is used in a conventional manner to denote a device that can stop fluid flow in a conduit or pipe. A check valve is a special valve that allows fluid to flow in one direction only.

Fitting and valves of the prior art typically have gaskets and seals that are separate and discrete parts. These gaskets and seals exhibit material creep, cold flow and relaxation. That is, as the fluid pressure fluctuates, the gaskets move. This movement can lead to the gasket slipping from an original position, leading to gasket or seal failure. This movement also creates a rebound of the gasket as the pressure is released, creating a potential pressure ripple. Analytical instruments, in particular, are sensitive to the rebound and pressure ripple effect.

These problems are amplified as the pressure contained by such devices increases. Analytical instruments, such as chromatography pumps and detectors typically operate at pressures of up to 3,000 to 4,000 pounds per square inch (psi). It is desirable to have analytical instruments operate at higher pressures, however, fittings, valves and check valves have a high failure rate at pressures greater than 3,000 psi.

Summary of the Invention

45 Embodiments of the present invention feature devices and methods for holding fluids at high pressures. One embodiment of the present invention features a device for receiving

and discharging fluids. The device comprises a first housing having at least one side wall. The side wall has an interior surface defining at least one chamber and has at least one end cap abutment surface for receiving an end cap. The device has at least one end cap having at least one first housing abutment surface. The first housing abutment surface receives the end cap abutment surface positioning the end cap on the first housing for enclosing the chamber. At least one of the first housing abutment surface and the end cap abutment surface has first seal coating. The first seal coating comprises a deformable plastic adhering to the abutment surface. The device further comprises a fluid path means for receiving and removing fluid from the chamber. And, the device comprises compression means to compress the end cap, with the end cap abutment surface received on said first housing abutment surface, towards said first housing to deform said first seal coating and seal said chamber.

Preferably, the seal coating is selected from one or more of the polymeric coatings consisting of polytrifluoroethylene (PTFE), polyetheretherketone (PEEK), polychlorotrifluoroethylene (PCTFE), perfluoroalkoxy (PFA) and fluorinatedethylenepropylene (FEP).

As used herein, the term "fluid path means" refers to openings, ports, conduits and pipes that provide fluid. Thus, embodiments of the present invention can be placed in line, with fluid path means comprising conduits and pipes or incorporated within the housing of a larger structure, for example, without limitation, a pump head or pump housing.

Preferably, the end cap abutment surface and/or the housing abutment surface is a ridge to localize compression forces on said seal coating. The ridge is a relatively narrow protrusion capable of contact with an opposing abutment surface.

Embodiments of the present invention are ideally suited for fittings and valves. Where the device is in the form of a valve, the chamber contains a valve assembly. The valve assembly may comprise rotary-type valves, gated valves or check valves.

In the case where the device is in the form of a check valve, the first housing has at least one end wall opposite the end cap. The fluid path means comprises at least one opening in said end cap and at least one opening in said end wall. And, the chamber holds a valve assembly comprises a ball seat and a ball.

Preferably, the interior wall and/or the end cap has a ball seat abutment surface. And, the ball seat comprises a cylinder having a two rims, and a fluid passage. At least one of the rims has a ball receiving surface for engaging the ball and closing the fluid passage. And, at least one of the rims has a rim abutment surface for engaging the ball seat abutment surface and sealing the ball seat and the housing and/or end cap.

Preferably, the ball seat abutment surface and/or rim abutment surface has a ball seat seal coating. Preferably, the ball seat coating is made and formed as described above with respect to the seal coating.

Preferably the first housing end wall has an interior surface and an exterior surface, and one or more end wall openings. And, the exterior surface has an end wall abutment

surface encircling the one or more end wall openings. Preferably, the end wall abutment surface has an end wall seal coating, the end wall seal coating comprising a deformable plastic to sealably engage an adjoining wall. Preferably, the end wall seal coating is made and formed as described above with respect to the seal coating. Devices of this type are well suited to be mounted in a further major housing structure having the adjoining wall. For example, without limitation, the end wall seal coating would engage the adjoining wall of a pump head housing. In this embodiment, preferably, the adjoining wall has an adjoining wall opening for the passage of fluid into the end wall opening. In this embodiment, the compression means comprises such adjoining wall for receiving the end wall and compressing the end wall seal coating in sealing engagement.

For inline application, preferably, the compression means comprises a compression housing assembly comprising a compression housing and compression sleeve. The compression housing has a compression chamber for receiving the housing. The compression sleeve engages the end cap for placing the end cap, and first housing under compression.

Preferably, the compression housing assembly has a compression nut. The compression nut and compression housing have cooperating threads which engage upon relative rotation of the compression nut and compression housing. The compression nut engage the compression sleeve to compress the compression sleeve, end cap and first housing within the compression housing chamber.

A further embodiment of the present invention comprises a method of joining fluid passages. One embodiment of the present method comprises the steps of providing a device having a first housing having a at least one side wall. The side wall has an interior surface defining at least one chamber, and has at least one end cap abutment surface for receiving an end cap. The device has at least one end cap. The end cap has at least one first housing abutment surface and is capable of being received on the first housing abutment surface for enclosing said chamber. The device has a first seal coating on at least one of the first housing abutment surface and the end cap abutment surface. The first seal coating comprises a deformable plastic adhering to the abutment surface. The device has a fluid path means for receiving and removing fluid from the chamber; and compression means to compress the end cap, with said end cap abutment surface received on said first housing abutment surface, towards said first housing to deform said first seal coating and seal said chamber. The method further comprises the step of placing the receiving conduit and discharge conduits in communication with the fluid passages.

Embodiments of the present method can be practiced with any of the devices of the present invention described above. The devices and methods of the present invention are ideally suited for high pressure applications. These high pressure applications include pressures of 4000 psi and greater.

The devices made in accordance of the present invention do not have seals that exhibit material creep, cold flow and relaxation. That is, as the fluid pressure fluctuates, the seal coating do not move. The seal coatings are adhered to or fixed to one of the abutment

surfaces. As such the seal coating can not move or slip from an original position. Thus, embodiments of the present invention provide devices that do not have gasket failure.

- 5 Nor do devices of the present invention exhibit rebound pressure ripple due to gasket movement as the pressure is released. Analytical instruments, in particular, having devices made in accordance with the present invention are less sensitive to pressure fluctuations.

10 These features and advantages will be apparent to those skilled in the art to which this invention relates upon viewing the Figures and reading the detailed description that follows.

BRIEF DESCRIPTION OF THE DRAWINGS

15 Figure 1 depicts, in cross section, a side view of a device made in accordance with the present invention;

Figure 2 depicts, in slight elevation, a view of an end cap of a device made in accordance with the present invention;

20 Figure 3 depicts, in slight elevation a view of an end cap of a device made in accordance with the present invention;

Figure 4 depicts, in cross section, a side view of an end cap of a device made in accordance with the present invention; and,

25 Figure 5 depicts, in cross section, a side view of a device made in accordance with the present invention.

DETAILED DESCRIPTION OF THE INVENTION

30 Embodiments of the present invention will now be described with respect to the Figures, with the understanding that the Figures and description are directed to the preferred embodiments of the present invention. For example, the present invention will be described in detail with respect to a check valve. Individuals skilled in the art will recognize that features of the present invention have application in many devices which
35 hold or transport fluids under pressure.

Turning now to Figure 1, a device, for holding fluids at high pressures, generally designated by the numeral 11, is depicted. The device 11, for receiving and discharging fluids, is in the nature of a check valve. Device 11 comprises a first housing 13, an end
40 cap 15, at least one seal coating 17 and compression means 19.

Turning now to Figure 2, the first housing 13 has at least one side wall 25. Side wall 25 has an interior surface 27a and an exterior surface 27b. The interior surface 27a defines at least one chamber 29, preferably, cylindrical in shape. Interior surface 27a has at least
45 one end cap abutment surface 31 for receiving the end cap 15. Preferably, the end cap

abutment surface 31 is recessed into chamber 29 to facilitate positioning of the end cap 15. As depicted, interior surface 27 has a recess section 33 forming the recess for receiving end cap 15.

- 5 The housing 13 has an end wall 35 having an interior surface 37a and an exterior surface 37b. The end wall 35 closes the chamber 29 defined by the interior surface 27a of the side wall 25.

10 End cap 15 is cylindrical in shape to cooperate with the recess section 33 of the interior surface 27a of the first housing 13. End cap 15 has at least one first housing abutment surface 39. Turning now to Figures 3 and 4, alternative embodiments of end cap 15 are disclosed. The end cap 15 of Figure 2 is illustrated in greater detail in Figure 3. End cap abutment surface 39 is a ridge 39a to localize compression forces on said seal coating 17. The ridge 39a is a protrusion jutting upward from a planar surface 39b. The ridge 39a is
15 capable of contact with an opposing abutment surface such as end cap abutment surface 31 of the first housing 13. The ridge 39a localizes or focuses compression forces in a small area.

20 Turning now to Figure 4, a further embodiment of the end cap 15 is illustrated, generally designated by the numeral 15'. End cap 15' is cylindrical in shape to cooperate with the recess section 33 of the interior surface 27a of the first housing 13. End cap 15' has at least one first housing abutment surface 39'. In this embodiment, the first housing abutment surface 39' is planar, without any protruding surface features. The abutment surface 39' is capable of contact with an opposing abutment surface such as end cap
25 abutment surface 31 of first housing 13.

The first housing abutment surface 31 receives the end cap abutment surface 39 and 39" positioning the end cap 15 and/or 15' on the first housing 13 for enclosing the chamber 29. The end cap 15 and/or 15' and first housing are typically made of stainless steel;
30 however, other materials can readily be substituted. In the case where, the first housing 13 and end cap 15 and/or 15' are parts of a check valve, the first housing 13 is approximately 0.25 to 0.75 mm in length and diameter. The end cap 15 and or 15' are approximately 0.1 to 0.70 in diameter and 0.1 to 0.2 mm in thickness.

35 At least one of the first housing abutment surface 39 and/or 39' and the end cap abutment surface 31 has first seal coating 17. The first seal coating 17 comprises a deformable plastic adhering to first housing abutment surface 31 and/or 31' or the end cap abutment surface 39. Seal coating 17 is selected from one or more of the polymeric coatings consisting of polytrifluoroethylene (PTFE), polyetheretherketone (PEEK),
40 polychlorotrifluoroethylene (PCTFE), perfluoroalkoxy (PFA) and fluorinatedethylenepropylene (FEP). The polymeric coating is applied to the entire end cap 15 and/or 15' or the first housing abutment surface 31 and/or 31' to a thickness of .0005 -.0025 inches, and most preferably, approximately .0010 to .0015 inches. Methods of placing a polymeric coating on a metal substrate are well known in the art.

45

The device 11 further comprises fluid path means for receiving and removing fluid from the chamber. Referring now to Figures 3 and 4, the end cap 15 and 15' have an end cap opening 45. And, returning now to Figure 1, the first housing has a first housing opening or more preferably a pair of first housing openings 47a and 47b for introducing fluids into the chamber 29. Preferably, the pair of openings are set off axis for check valve applications in end wall 35.

The end cap opening 45 and first housing openings 47a and 47b may comprise any ports, conduits and pipes that provide fluid. Thus, embodiments of the present invention can be placed inline, with fluid path means comprising conduits and pipes or incorporated within the housing of a larger structure, for example, without limitation, as depicted in Figure 1, a pump head or pump housing 49.

The device 11 comprises compression means 19 to compress the end cap 15 and/or 15', with the end cap abutment surface 31 and/or 31' received on said first housing abutment surface 39, towards said first housing 13. The compression deforms the first seal coating 17 and seals the chamber. As illustrated in Figure 1, the compression means 19 comprises pump housing 49, compression housing 51 and screw fitting 53.

It will be recognized by those skilled in the art that pump housing 49 may be substituted with a further fitting that cooperates with compression housing 51 and screw fitting 53, to allow the device 11 to be placed in a fluid line.

Embodiments of the present invention are ideally suited for fittings and valves. Where the device is in the form of a valve, referring to Figure 2, the chamber 29 contains a valve assembly 61. The valve assembly 61 may comprise rotary-type valves (not shown), gated valves (not shown) or check valves, to described in further detail.

In the case where the device is in the form of a check valve, the first housing 13 has at least one end wall 65 opposite the end cap 15 or 15'. The fluid path means comprises at least one opening 45 in said end cap 15 or 15' and at least one opening, and preferably two, 47a and 47b, in said end wall 65. Chamber 29 holds a valve assembly 61 comprising a ball seat 71 and a ball 73.

Preferably, the interior wall 27a has a first ball seat abutment surface 77. And, the end cap 15 and/or 15' has a ball seat abutment surface 79. The ball seat 71 comprises a cylinder section 81 having a first rim 83, a second rim 85 and a fluid passage 87. The first rim 83 has a ball receiving surface 89 for engaging the ball 73 and closing the fluid passage 87. Second rim 85 has a rim abutment surface 91 and end cap 15 and/or 15' has a ball seat abutment surface 79. Preferably, at least one of the rim abutment surface 91 and ball seat abutment surface 79 has a ball seat seal coating 95. The ball seat seal coating 95 engages the abutment surface opposite to that it is placed and seals the ball seat and the housing 13 and/or end cap 15 and/or 15'. The ball seat coating 95 may comprise a portion of the seal coating 17 on the end cap 15 and/or 15'. Preferably, the ball seat coating is made and formed as described above with respect to the seal coating 17.

The exterior surface 37b of end wall 35 has an end wall abutment surface 99 encircling the one or more end wall openings 47a and 47b. Preferably, the end wall abutment surface 99 has an end wall seal coating 101. The end wall seal coating 101 is a deformable plastic made and formed as described above with respect to the seal coating 17. The end wall seal coating 101 sealably engages an adjoining wall to which it is compressed.

Devices of this type are well suited to be mounted in a further major housing structure having the adjoining wall. For example, turning now to Figure 1, the end wall seal coating 101 engages the adjoining wall 105 of a pump head housing 49. In this embodiment, preferably, the adjoining wall 105 has an opening 103 for the passage of fluid into the end wall opening (not shown). In this embodiment, the compression means 19 comprises such adjoining wall 105 and a cylindrical wall 107 for receiving the end wall abutment surface 99 and compressing the end wall seal coating 101 in sealing engagement. The compression means 19 comprises a compression assembly comprising a compression housing 51 and compression sleeve 53. The compression housing 51 has a compression chamber 113 for receiving the first housing 13 and the end cap 15 and/or 15'. The compression sleeve 53 engages the compression housing 51 for placing said end cap 15 and/or 15', and first housing 13 under compression.

Preferably, the compression sleeve 53 and compression nut (not shown) or the pump head 49 or other apparatus to which it is placed has cooperating threads 115 as depicted in Figure 1. The cooperating threads 115 engage upon relative rotation of the compression sleeve and pump housing 49 or compression nut (not shown).

Turning now to Fig 2, the compression housing 51 has a second end cap abutment surface 117. At least one of the end cap 15 and/or 15' has a compression assembly seal coating 121. The compression assembly seal coating 121 is a deformable plastic made and formed as described above with respect to the seal coating 17. The compression assembly seal coating 121 sealably engages an adjoining wall to which it is compressed.

In operation, a method of using the present invention to joining fluid passages comprises the steps of providing a device 11 having a first housing 13, an end cap 15 and or 15', a seal coating 17 and compression means 19. The device has a fluid path means for receiving and removing fluid from the chamber 29. The method further comprises the step of placing the receiving conduit and discharge conduits in communication with the fluid passages and compressing the seal coating 17 to seal the chamber 29.

The devices and methods of the present invention are ideally suited for high pressure applications. The devices made in accordance of the present invention do not have seals that exhibit material creep, cold flow and relaxation. That is, as the fluid pressure fluctuates, the seal coating do not move. The seal coatings are adhered to or fixed to one of the abutment surfaces. As such the seal coating can not move or slip from an original position. Thus, embodiments of the present invention provide devices which do not have gasket failure.

These and other advantages and features will be apparent to those skilled in the art to which this invention relates and therefore the present invention should not be limited to the precise details disclosed herein but should encompass the subject matter of the claims that follow.

CLAIM

1. A device for receiving and discharging fluids comprising:

- 5 a.) a first housing having a at least one side wall, said side wall having an interior surface defining at least one chamber, and having at least one end cap abutment surface for receiving an end cap;
- b.) at least one end cap, said end cap having at least one first housing abutment surface and said first housing abutment surface positioned on said end cap abutment surface for
10 enclosing said chamber;
- c.) a first seal coating on at least one of said first housing abutment surface and said end cap abutment surface, said first seal coating comprising a deformable plastic adhering
15 said abutment surface;
- d.) fluid path means for receiving and removing fluid from said chamber; and
- e.) compression means to compress said end cap, with said end cap abutment surface
20 received on said first housing abutment surface, towards said first housing to deform said first seal coating and seal said chamber.
2. The device of claim 1 wherein said seal coating is selected from one or more of the polymeric coating consisting of polytrifluoroethylene (PTFE), polyetheretherketone (PEEK), polychlorotrifluoroethylene (PCTFE), perfluoroalkoxy (PFA) and
25 fluorinatedethylenepropylene (FEP).
3. The device of claim 1 wherein at least one of said end cap abutment surface and said housing abutment surface is a ridge to localize compression forces on said seal coating.
4. The device of claim 1 wherein said at least one chamber contains a valve assembly.

5. The device of claim 4 wherein said housing has at least one end wall opposite said end cap and said fluid path means comprises at least one opening in said end cap and at least one opening in said end wall.

6. The device of claim 5 wherein said valve assembly comprises a ball seat and a ball.

7. The device of claim 6 wherein at least one of said interior wall and said end cap has an ball seat abutment surface, said ball seat comprising a cylinder having a two rims, and fluid passage, at least one of said rims having a ball receiving surface for engaging said ball and closing the fluid passage and at least one of said rims having a rim abutment surface for engaging said ball seat abutment surface and sealing the ball seat and at least one of said housing and end cap.

8. The device of claim 7 wherein at least one of said ball seat abutment surface and rim abutment surface has a ball seat seal coating.

9. The device of claim 8 wherein said ball seat seal coating is selected from one or more of the polymeric coating consisting of polytrifluoroethylene (PTFE), polyetheretherketone (PEEK), polychlorotrifluoroethylene (PCTFE), perfluoroalkoxy (PFA) and fluorinatedethylenepropylene (FEP).

10. The device of claim 5 wherein said end wall has an interior surface and an exterior surface, said end wall having one or more end wall openings and said exterior surface having an end wall abutment surface encircling said one or more end wall openings.

11. The device of claim 10 wherein said end wall abutment surface has a end wall seal coating, said end wall seal coating comprising a deformable plastic to sealably engage an adjoining wall.

12. The device of claim 11 wherein said end wall seal coating is selected from one or more of the polymeric coating consisting of polytrifluoroethylene (PTFE), polyetheretherketone (PEEK), polychlorotrifluoroethylene (PCTFE), perfluoroalkoxy (PFA) and fluorinatedethylenepropylene (FEP).

13. The device of claim 13 wherein said compression means comprises an adjoining wall for receiving said end wall and compressing said end wall seal coating in sealing engagement.

14. The device of claim 13 wherein said adjoining wall has a adjoining wall opening for the passage of fluid into said end wall opening.

15. The device of claim 14 wherein said compression means comprises a major housing assembly comprising a major housing and compression sleeve, said major housing having a first housing chamber for receiving said first housing, and said compression sleeve for engaging said end cap for placing said end cap, and first housing under compression.

16. The device of claim 15 wherein said major housing assembly has a compression nut means, said compression nut means and major housing having cooperating threads which engage upon rotation of the compression nut means and major housing, said compression nut means engaging said compression sleeve to compress said compression sleeve, end cap and first housing within said major housing chamber.

17. A method of joining a fluid conduits comprising the steps of providing a device having:

a.) a first housing having a at least one side wall, said side wall having an interior surface defining at least one chamber, and having at least one end cap abutment surface for receiving an end cap;

b.) at least one end cap, said end cap having at least one first housing abutment surface and said first housing abutment surface positioned on said end cap abutment surface for enclosing said chamber;

c.) a first seal coating on at least one of said first housing abutment surface and said end cap abutment surface, said first seal coating comprising a deformable plastic adhering said abutment surface;

d.) fluid path means for receiving and removing fluid from said chamber; and

- e.) compression means to compress said end cap, with said end cap abutment surface
5 received on said first housing abutment surface, towards said first housing to deform said first seal coating and seal said chamber; and,

placing said receiving conduit and discharge conduits in communication with said fluid path means.

- 10 18. The method of claim 17 wherein said seal coating is selected from one or more of the polymeric coating consisting of polytrifluoroethylene (PTFE), polyetheretherketone (PEEK), polychlorotrifluoroethylene (PCTFE), perfluoroalkoxy (PFA) and fluorinatedethylenepropylene (FEP).

- 15 19. The method of claim 18 wherein at least one of said end cap abutment surface and said housing abutment surface is a ridge to localize compression forces on said seal coating.

20. The method of claim 17 wherein said at least one chamber contains a valve assembly.

- 20 21. The method of claim 20 wherein said housing has at least one end wall opposite said end cap and said fluid path means comprises at least one opening in said end cap and at least one opening in said end wall.

22. The method of claim 21 wherein said check valve assembly comprises a ball seat and a ball.

- 25 23. The method of claim 22 wherein at least one of said interior wall and said end cap has an ball seat abutment surface, said ball seat comprising a cylinder having a two rims, and fluid passage, at least one of said rims having a ball receiving surface for engaging said ball and closing the fluid passage and at least one of said rims having a rim abutment

surface for engaging said ball seat abutment surface and sealing the ball seat and at least one of said housing and end cap.

24. The method of claim 23 wherein at least one of said ball seat abutment surface and rim abutment surface has a ball seat seal coating.

- 5 25. The method of claim 24 wherein said ball seat seal coating is selected from one or more of the polymeric coating consisting of polytrifluoroethylene (PTFE), polyetheretherketone (PEEK), polychlorotrifluoroethylene (PCTFE), perfluoroalkoxy (PFA) and fluorinatedethylenepropylene (FEP).

- 10 26. The method of claim 25 wherein said end wall has an interior surface and an exterior surface, said end wall having one or more end wall openings and said exterior surface having an end wall abutment surface encircling said one or more end wall openings.

27. The method of claim 26 wherein said end wall abutment surface has a end wall seal coating, said end wall seal coating comprising a deformable plastic to sealably engage an adjoining wall.

- 15 28. The method of claim 27 wherein said end wall seal coating is selected from one or more of the polymeric coating consisting of polytrifluoroethylene (PTFE), polyetheretherketone (PEEK), polychlorotrifluoroethylene (PCTFE), perfluoroalkoxy (PFA) and fluorinatedethylenepropylene (FEP).

- 20 29. The method of claim 28 wherein said compression means comprises an adjoining wall for receiving said end wall and compressing said end wall seal coating in sealing engagement.

30. The method of claim 29 wherein said adjoining wall has a adjoining wall opening for the passage of fluid into said end wall opening.

- 25 31. The method of claim 30 wherein said compression means comprises a major housing assembly comprising a major housing and compression sleeve, said major housing having a first housing chamber for receiving said first housing, and said compression sleeve for engaging said end cap for placing said end cap, and first housing under compression.

32. The method of claim 31 wherein said major housing assembly has a compression nut means, said compression nut means and major housing having cooperating threads which engage upon rotation of the compression nut means and major housing, said compression nut means engaging said compression sleeve to compress said compression sleeve, end
- 5 cap and first housing within said major housing chamber.

ABSTRACT

Embodiments of the present invention feature devices and methods for holding fluids at high pressures. One embodiment of the present invention features a device for receiving and discharging fluids. The device comprises a first housing having at least one side wall. The side wall has an interior surface defining at least one chamber and has at least one end cap abutment surface for receiving an end cap. The device has at least one end cap having at least one first housing abutment surface. The first housing abutment surface receives the end cap abutment surface positioning the end cap on the first housing for enclosing the chamber. At least one of the first housing abutment surface and the end cap abutment surface has first seal coating. The first seal coating comprises a deformable plastic adhering to the abutment surface. The device further comprises a fluid path means for receiving and removing fluid from the chamber. And, the device comprises compression means to compress the end cap, with the end cap abutment surface received on said first housing abutment surface, towards said first housing to deform said first seal coating and seal said chamber.




FIG. 1




Fig 2




FIG. 3